# **L2-EGW1**





What would a smart infrastructure be without an internet connected gateway. The L2-EGW Ethernet Gateway allows wired and wireless connection, control, and monitoring of up to 240 LumenCache modules. Add monitoring and control of every PDMbus device in one step by connecting the L2-EGW Ethernet Gateway. Automatically finds and identifies communicating devices creating an instant control interface via Smartphone and Tablets. Connect using wires or wireless to your local network router via wired Ethernet or Wifi wireless connection. Magnetically attaches to the top of the enclosure and connects to the communications expansion bus connector on the topmost PDM in the enclosure. The L2-EGW1 is powered by the L2-APR-12W through the comm bus cable (use only 12W APR when a gateway is attached). An expansion port allows connection of third-party control systems in addition to the LumenCache control APPs. The L2-EGW1 creates a WiFi hotspot for installations that do not have WiFi networks installed yet. The browser-based management console simplifies advanced installer settings. A connection to the internet is not required for operation. Connecting the EGW to the internet allows secure remote monitoring and control of your home of office in addition to managing accounts and device groups.

#### **POWER REQUIREMENTS**

Peak Power Consumed 1.9 W (5W Peak)

Requires 12W L2-APR on the same L2-PDM

Average Power Consumed 1.2 W

Input, Output Connectors Female 10 pin

USB Connectors 4

#### **RS485 CONTROL BUS**

Communication Speed 38,400 bps

Control Protocol Published LCbus protocol

Maximum devices per PDMbus 100 (1600 channel zones per system)

## **NETWORK**

Wired Gigabit RJ45 Ethernet port
Wireless 2.4GHz and 5GHz 802.11 b/g/n/ac
Access AWS Services (optional)

### **SYSTEM**

Memory 1 GB DDR2 Storage Memory 16 GB

#### PHYSICAL/ENVIRONMENTAL

Dimensions  $3.5 \times 2.75 \times 1$  in (89 x 69 x 25mm) Operating Temperature  $+32^{\circ}$ F to  $+122^{\circ}$ F (0°C to  $+50^{\circ}$ C) Operating Humidity 5% to 95% Non-condensing

Rating Dry Rated
Environmental RoHS
Safety Certifications CE, FCC

#### WARRANTY

Duration 5 Years

# **ORDERING INSTRUCTIONS:**

PART ID	MODEL	DESCRIPTION
16010000.0	L2-EGW1	Ethernet Gateway, Wired and WiFi